



<https://uni-luce.com>
+39 339 505 5880
info@uni-luce.com

Via Monselice, 26, 20832 Desio
MB, Italy

OXY 2.5 SS VD



Available colors:	<input type="radio"/> 20192-W3-VD
	<input checked="" type="radio"/> 20192-B3-VD
	<input type="radio"/> 20192-R3-VD
Beam angle:	10° 15° 20° 30° 40° 60° 10*45° 25*45°
LED Color:	2700K 3000K 4000K 6000K
Lamp Power:	2.5W
CRI:	90
Lamp Lumen:	240lm
Material:	aluminium, glass
Location:	Exterior
Fixation:	Ground, Wall
Installation:	Floodlight
Product dimension:	D33xL50mm
Input:	24V 50/60Hz
IP:	65
Class:	III
DIM Option:	DALI RGB DMX PWM RGWB
IK:	08





<https://uni-luce.com>

+39 339 505 5880

info@uni-luce.com

Via Monselice, 26, 20832 Desio

MB, Italy

OXY collection can be used throughout a complete outdoor project, to light up trees, emphasize architecture or highlight pathways.

Although compact in size, the clever design of OXY offers a solution without any visible cabling outside of the luminaire. The hinge of the projector not only serves to tilt it into the wanted direction, it also hides away a passage for the cabling. Wide variety of beam angles from narrow beam to wide, as long as asymmetrical.