



<https://uni-luce.com>  
+39 339 505 5880  
info@uni-luce.com

Via Monselice, 26, 20832 Desio  
MB, Italy

## OXY 4 S



Available colors:	<input type="radio"/> 20193-W4
	<input type="radio"/> 20193-B4
	<input type="radio"/> 20193-R4
Beam angle:	10° 15° 20° 30° 40° 60° 10*45° 25*45°
LED Color:	2700K 3000K 4000K 6000K
Lamp Power:	2.5W
CRI:	90
Lamp Lumen:	386lm
Material:	aluminium, glass
Location:	Exterior
Fixation:	Ground, Wall
Installation:	Floodlight
Product dimension:	D43mmxL65mm
Input:	220-240V 50/60HZ
IP:	65
Class:	III
DIM Option:	DALI RGB DMX PWM RGBW
IK:	08





<https://uni-luce.com>

+39 339 505 5880

[info@uni-luce.com](mailto:info@uni-luce.com)

Via Monselice, 26, 20832 Desio

MB, Italy

OXY collection can be used throughout a complete outdoor project, to light up trees, emphasize architecture or highlight pathways.

Although compact in size, the clever design of OXY offers a solution without any visible cabling outside of the luminaire. The hinge of the projector not only serves to tilt it into the wanted direction, it also hides away a passage for the cabling. Wide variety of beam angles from narrow beam to wide, as long as asymmetrical.